



**MAXIMUM SPACING ALONG STREET GRADE**

STREET SLOPE	CURB SOCK SPACING (ft)
0.5%	100
1.0%	100
2.0%	75
3.0%	50
4.0%	50
5.0%	50
6.0%	25
7.0%	25
8.0%	25

NOTES

1. A MINIMUM OF THREE ROCK SOCKS SHALL BE PLACED DOWNSTREAM OF ANY DISTURBED AREA AND ALONG ALL CURBS FRONTING DISTURBED AREAS, SPACED PER THE TABLE.
2. ROCK SOCKS WILL BE USED UPSTREAM OF INLETS, ANGLED AS SHOWN AND SHALL BE FLUSH WITH THE CURB.
3. ROCK SOCKS MUST BE PLACED NO MORE THAN 5 FEET APART UPSTREAM OF INLETS.

MERRICK PROJECT NO. 65414304

CLIENT PROJECT NO.

REVISION DESCRIPTION

DRAWN DATE SCALE N.T.S



**MERRICK**

Engineers & Architects

5970 Greenwood Plaza Blvd, Greenwood Village, CO 80111

BEAR CREEK  
WATER & SANITATION DISTRICT

TITLE: TYPICAL ROCK SOCK DETAIL

REVISION: DRAWING NO.

SHEET NO.

4/5